



Dal Cin Gildo spa
20863 Concorezzo (MB) - Via l' Maggio, 67 - Italy
tel. +39 039 6049477 - fax +39 039 6886150
www.dalcin.com - info@dalcin.com
rea 499659 - Reg. Imprese MI 00767140155 sede legale: 20149 Milano - Via Monte Rosa, 21
cap. soc. € 2.500.000 int. vers. - c.f./p.iva IT 00767140155

DICISAN SPECIAL

4520

DETERGENZA

Alkaline activated chlorine detergent

Data Sheet

Revision 21.10

Date 7/01/2021

TECHNICAL SPECIFICATION

	TECHNIQUES or ANALYTICAL METHOD (*)	LIMIT VALUES (legal or internal)	MEDIUM VALUES (by Quality Control)
Physical state	DC 1.01	liquid	liquid
Colour	DC 1.02	pale yellow	pale yellow
Smell	DC 1.03	typical	typical
Active chlorine at the origin (sol.1%)	DC 2.11	min 650 ppm	700 - 750 ppm
pH 1% solution	DC 1.05	12 -14	12 -13
Density	DC 1.10	1.15 - 1.25	1.20
Reaction	technical information	alkaline	compliant
Surfactants	technical information	anphoteric	compliant
Biodegradability	technical information	min 90%	compliant

Compatibility on materials
see notes

(*) Methods available on request

CLASSIFICATIONS AND DECLARATIONS

Compliance with regulations	The product is suitable for hygiene in food industry
Limitations of use	=
Minimum term of conservation	=
Safety Classification (CLP)	Danger - pictograms: GHS07 - GHS09 Hazard statement: H314 – H400 – EUH206 Precautionary statements: P264 - P273 - P280 - P304+340 - P310
ADR classification	Class: 8 – Packing group: II not applicable
Allergens	not applicable
Products of animal origin	none
Kosher certification	not applicable
Other statements	Quality Management System Dal Cin Gildo Spa certified according to ISO9001: 2015 (No. 1713 Certiquality)

PACKAGING AND STORAGE

Bottle of 1 kg (code 4523)

Tank of 10 kg (code 4522)

Tank of 25 kg (code 4521)

Cask of 250 kg (code 4524)

Big of 1100 kg (code 4520)

Keep at temperature over 12°C (below this temperature the product becomes solid). The frozen product can be dissolved without any problem at room temperature.

Avoid direct sunlight. Keep far from acid products.

NOTE

Corrosive on zincate materials, aluminium, phenolic resins

Not corrosive on stainless steel, plastic material, epoxy resins, cement, glass, rubber, nitro paints